

Specification sheet

SCION 436-GC

Dimensions and weights

Size*: Height: 57 cm (22.4 in.)
 Width: 32 cm (12.6 in.)
 Depth: 61 cm (24.0 in.)
 Weight*: 26.8 kg (59 lb)

*Typical values

Environmental Conditions

Operating temperatures: 10 °C to 40 °C
 Operating humidity (relative): 5 % to 95 %
 Line voltage requirements: 120 V, 230 V (±10 % nominal)

Column Oven

Dimensions: 23 cm (w) x 11 cm (d) x 28 cm (h)

Temperature range:

- Ambient +10 °C to 450 °C
- Liquid N₂: -100 °C to 450 °C
- Liquid CO₂: -60 °C to 450 °C

Temperature program ramps/holds: 24/25

Maximum temperature ramp rate: 170°C/min for all voltages

Cool down rate: 400 °C to 50 °C in 4.5 minutes

Temperature set-point resolution: 0.1 °C

Ambient temperature reject <0.01 °C change in oven for 1 °C change in ambient temp

Retention Time Repeatability <0.008% or < 0.0008 min, based on Pentadecane under temperature program conditions

Area repeatability < 1% RSD

General Specifications

Up to 3 EFC modules total, injector, detector and auxiliary

Optional backflush

GC Control:

- External events (digital output):
 - 8 standard
 - 8 optional, total 16
- Max number of timed events: 30
- Heated zones:
 - Standard 5
- Two power outlets 24V (1A max. each)



Temperature Range (°C)	436-GC Rates (°C/min)
50 - 70	170
70 - 115	105
115 - 175	80
175 - 300	55
300 - 450	35

Methods:

- Maximum stored internal methods: 50 (max. 30 alphanumeric characters)

Logging:

- Run log file (stored with the chromatogram when using CompassCDS)
- Error log file

Local Display:

- TFT full color screen
- WGA resolution (800 x 480)
- Size 23 cm (9")

Local Control:

- Touch screen
- Hard keys

Languages:

- English, German, French, Spanish, Italian, Portuguese, Cyrillic, Kanji, Chinese (standard and traditional), Thai, Korean and Dutch.

Local automation:

- Method lines: 25
- Modes:
 - Infinite looping
 - Dual and duplicate injection

Communication

Ethernet: Protocol: TCP/IP

Data rate: 100 Mbps

Control: GC control and method parameters

Analog output (optional):

- Number of channels: 1
- Time programmable steps: 30
- Output software selectable (set individual):
 - 0-1 V (default)
 - 0-10 V

Synchronisation signals with other devices and data systems:

- Ready in and out
- Start in and out

Data Handling and System Control:

- CompassCDS Chromatography Data System

Certifications

- CSA:
 - C22.2 61010-1
 - UL 61010-1
- EC: 61010-1
- EMC:
 - 47 CFR part 15
 - ANSI C63.4
 - EN 61326

Injector Options

Maximum injectors: two, operating concurrently

Pneumatics: Electronic Flow Control (EFC), or manual

Injector types:

- S/SL Split/Splitless injector*
- PTV Programmable Temperature Vaporising*
- COC Cold On-Column injector*
- Flash injector
- PWOC Packed/ Wide bore On-Column injector

*Including septum purge

S/SL Split/Splitless Injector

Pressure range: 0-150 psi

Total flow:

- 500 mL/min for N₂/Ar
- 1500 mL/min for He/H₂

Maximum temperature: 450 °C

Split range: 1-10,000 (column dependent)

Suited for columns:

Wide bore: (0.53 mm)

Narrow bore: (0.05 to 0.32 mm)

COC Cold On-Column Injector

Pressure range: 0-150 psi

Total Flow: 50 mL/min (Type 23 EFC)

Temperature range:

- Ambient +10 °C to 450 °C using air cooling
- -60 °C to 450 °C using liquid CO₂ cooling
- -160 °C to 450 °C using liquid N₂ cooling

Maximum temperature: 450 °C

Maximum temperature ramp rate: 200 °C/min

Temperature ramps/holds: 24/25

Suited for columns:

- Wide bore (0.53 mm)
- Narrow bore (0.32 mm)

PTV Programmable Temperature

Vaporising Injector

Pressure range: 0-150 psi

Total flow:

- 500 mL/min for N₂/Ar
- 1500 mL/min for He/H₂

Temperature range:

- Ambient + 10 °C to 450 °C using air cooling
- -160 °C to 450 °C using liquid N₂ cooling
- -60 °C to 450 °C using liquid CO₂ cooling

Maximum temperature ramp rate: 200 °C/min

Temperature ramps/holds: 24/25

Split range: 1-10,000 (column dependent)

Operational capabilities:

- Large volume injection
- Temperature ramped splitless
- Cold on-column
- Split and splitless
- ChromatoProbe solid sample introduction optional

Suited for columns:

- Wide bore (0.53 mm)
- Narrow bore (0.05 to 0.32 mm)

Maximum injection volume: 250 µL (LVI mode)

Flash Injector

Pressure range: 0-150 psi

Total flow:

- 50 mL/min (Type 23 EFC)

Maximum temperature: 450 °C

Suited for columns:

- Wide bore (0.53 mm)
- Packed (1/8" to 1/4")

PWOC Packed/Wide-bore On-Column Injector

Pressure range: 0-150 psi

Total flow:

- 50 mL/min (Type 23 EFC)

Maximum temperature: 450 °C

Suited for columns:

- Wide bore (0.53 mm)
- Packed (1/8" to 1/4")

Electronic Flow Control: Injectors (EFC)

Module types: 2 injector-specific modules

Pressure: 0.1 % Full Scale

Resolution pressure set points is 0.001 psi

Flow sensor accuracy 2% of measured or 0.2% of full scale

Flow sensor repeatability 0.5%

Quick-Switch Valve Option

Instantly switch between injectors/columns and detectors

Configurations: automated or manual, factory or field installed

Detector Options

Maximum detectors: Two, operating concurrently (one of which is MS or external Detector)

Pneumatics: Electronic Flow Control (DEFC) or manual

Detector types:

- FID Flame Ionization Detector
- TCD Thermal Conductivity Detector
- ECD Electron Capture Detector
- NPD (TSD) Nitrogen-Phosphorus Detector
- PFPD Pulsed Flame Photometric Detector
- PDHID Pulsed Discharge Helium Ionization Detector
- MS Mass Spectrometry (see GC/MS brochure and datasheet)

Note: Data Acquisition Rate : 600Hz for all detectors, exception is the PFPD

FID Flame Ionization Detector

Maximum temperature: 450 °C

Detectivity: 1.2 pg C/sec

Linear dynamic range: 10⁷

Flame tip type: ceramic (patented)

Operational quality:

- Flame-out detection
- Auto re-ignition

TCD Thermal Conductivity Detector

Maximum temperature: 450 °C

Detectivity: 300 pg/mL (Butane)

Linear dynamic range: 10⁶

Operational quality:

- Filament protection
- Automatic bridge balancing

ECD Electron Capture Detector

Maximum temperature: 450 °C

Detectivity: 7 fg/s Lindane

Linear dynamic range: 10⁴

Radioactive source: 63Ni - 15 mCi (555 Mbq)

NPD (TSD) Nitrogen-Phosphorus Detector

Maximum temperature: 450 °C

Detectivity:

N: 100 fg N/sec (Azobenzene)

P: 100 fg P/sec (Malathion)

Linear dynamic range:

- N: 10⁵
- P: 10⁴

Operational quality: self-aligning bead

PFPD Pulsed Flame Photometric Detector

Photomultiplier tube:

- S/P
- S/P/N

Maximum temperature: 450 °C

Detectivity:

- S: 1 pg S/sec (S/P tube)
- P: 100 fg P/sec (S/P tube)
- N: 20 pg N/sec (S/P/N tube)

Linear dynamic range:

S: 10³

P: 10⁴

N: 10²

Up to 23 elements can be detected

PDHID Pulsed Discharge Helium Ionization Detector

Detectivity: 50 ppb (Methane)

Linear dynamic range: 10⁴ (Methane)

Operational quality:

- Gold plated connections
- Welded column connections

Detectors (DEFC)

Module types: 6 detector-specific modules

Accuracy: ± 7 % set point flow

Resolution: 0.1 or 1 mL/min

Automation Options

CP-8410 Auto Injector

Sample capacity:

- 10 x 2 mL vials
- 6 x 5 mL vials
- 5 x 10 mL vials

Large solvent wash vial: 2 x 120 mL*

Dual and duplicate mode

Internal standard addition

Modes of operation:

- Liquid
- Ambient headspace*
- SPME (Solid Phase MicroExtraction)*
- Sample heating and cooling*

Pre-programmed modes of injection Syringes:

- 1 µL, 2 µL, 5 µL, 10 µL, 100 µL, 250 µL
- for liquid injection
- SPME

CP-8400 AutoSampler

Sample capacity: 100 x 2 mL vials

Large solvent wash vial: 2 x 120 mL*

Dual and duplicate mode

Internal standard addition

Modes of operation:

- Liquid
- Ambient headspace*
- SPME*
- Sample heating and cooling*
- Pre-programmed modes of injection

Syringes:

- 1 µL, 2 µL, 5 µL, 10 µL, 100 µL, 250 µL for liquid injection
- SPME

* Optional

PAL Combi-xt AutoSampler

Sample trays: two standard and expandable to four

Tray types:

- 98 x 2 mL vials
- 200 x 1 mL vials
- 32 x 10 mL/20 mL vials
- 96-well plates

Dual and duplicate mode

Internal standard addition

Modes of operation:

- Liquid
- Heated headspace*
- SPME*
- ITEX*

Sample heating and cooling

Additional optional modules: further sample trays, micro-

well plate holders, wash station,

SPME fiber bake-out station, dilutor, barcode readers, and

flowcell

* Optional

